ULTRA OIL ANTIFREEZE G12 RED -40 DERECE

Product Description and Usage Area

It is an ethylene glycol-based, ready-to-use red antifreeze with special organic type corrosion inhibitor, especially formulated for vehicles with radiators made of aluminum and its alloys. It is recommended for use in cold regions down to -40°C. It is suitable for use in gasoline and diesel engines. It is ready for direct use. Not recommended for use in regions colder than -40°C.

Features and Benefits

- It can be used in all kinds of radiators in all seasons.
- Thanks to special anti-corrosion additives, it protects the copper and brass materials in the engine against corrosion and does not damage the gaskets.
- It prevents cracking and other damage caused by expansion in cold climates.
- Compatible with all sealing components.
- Does not contain nitrite, boron, phosphorus, silicate, amine
- It is ready for direct use.

Typical Features

TEST	Metod	TYPICAL VALUES
Apperance	-	Clear
Color	ASTM D 1122	Red
Boilng Point C	ASTM D 1120	118
PH Value	ASTM D 1287	7-11
Freezing Point C	ASTM D 1177	-40

*** Values may differ from production to production.**

Storage conditions

It should be protected from direct sunlight and precipitation. Packages should be stored closed, under the porch or in a closed area. Storage temperature should be between (+5)- (+40)°C.

Health and Safety Information

In the light of available information, this product is not expected to cause adverse effects on human health when used in the intended location and specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be categorized according to the Waste Oil Control Regulation and disposed of through licensed enterprises with the characteristics defined in this regulation. Please read the Material Safety Sheet when necessary.