ULTRA OIL FORCE 10W-30 LA

ULTRA OIL FORCE 10W-30 LA is synthetic base heavy duty oil whic feature "Low-SAPS" additive technology while delivering energy savings. Protective power is enhanced through the use of synthetic base oil technology to deliver fuel economy performance with no compromise in durability.

PROPERTIES

- Provides long life for exhaust emission systems by its low ash, phosphorus and sulphur (Low-SAPS) content.
- Thanks to its high oxidation and viscosity stability, saves maintenance cost by meeting requirements of long drain intervals.
- It can be used safely at all climate and road conditions by providing constant lubrication. Protects the engine against wear, rust and corrosion and prolongs the motor life and performance.
- Producing with low friction technology and due to its excellent fluidity and pumpability properties provides maximum protection against wear at the time of first run of engine.

SPECIFICATIONS/ APPROVALS

API CJ-4, CI-4 Plus, CI-4, ACEA E9, E7, Caterpillar ECF-3, ECF-2, Cummins CES 20081, Deutz DQC III-18 LA, MAN M3775, MB-Approval 228.31, Renault RLD-3, Volvo VDS-4, JASO DH-2

TECHNICAL SPECIFICATIONS

Test	Method	Typical Properties
Kinematic Viscosity (100°C, cSt)	ASTM D445	11,5
Viscosity Index	ASTM D2270	150
Flash Point (°C)	ASTM D92	225
Pour Point (°C)	ASTM D97	-36
Density (15°C, g/cm3)	ASTM D 1298	0,86

*Typical values may vary slightly from production to production

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

GEBKİM İhtisas OSB Nuri Türker Caddesi No:4 Dilovası/KOCAELİ

Tel: +90 262 646 11 01 (pbx) Faks: +90 262 646 01 00