



## **ULTRA OIL FORCE 10W-40 EC6**

ULTRA OIL FORCE 10W-40 EC6 is the high performance, synthetic heavy duty diesel motor oil deliver responsive protection, maintenance saving long drain performance, protection against wear, deposits, and fuel economy. Suitable for most Euro 4, 5 engines without Diesel Particle Filter.

### **PROPERTIES**

- Thanks to its high oxidation and viscosity stability, saves maintenance cost by meeting requirements of long drain intervals.
- It can be used safely at all climate and road conditions by providing constant lubrication.
- Protects the engine against wear, rust and corrosion and prolongs the motor life and performance.
- ULTRA OIL FORCE 10W-40 EC6 can save money in fuel consumption compared high viscosity grades.

### **SPECIFICATIONS/ APPROVALS**

API CI-4, ACEA E4-E7, DEUTZ DQC IV-10, MAN 3377, MB-Approval 228.5, Renault RLD-2, Volvo VDS-3

### **TECHNICAL SPECIFICATIONS**

Test	Method	Typical Properties
Kinematic Viscosity (100°C, cSt)	ASTM D445	14,5
Viscosity Index	ASTM D2270	150
Flash Point (°C)	ASTM D92	231
Pour Point (°C)	ASTM D97	-36
Density (20°C, g/cm <sup>3</sup> )	ASTM D 1298	0,86

\*Typical values may vary slightly from production to production

### **STORAGE**

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)

**HEALTH AND SAFETY**

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.