

ULTRA OIL GEARTECH EP 85W-90 GL-5

Date of Issue: 08.01.2021

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name and codeULTRA OIL GEARTECH EP 85W-90 GL-5

Product use Automotive Gear Oil

Producer/supplier Xenol Enerji San. Ve Tic. A.Ş.

Address GEBKİM ihtisas OSB Nuri Türker Caddesi No:4

41455 Dilovası / KOCAELİ-TURKEY

Tel: +90 262 646 11 01 Fax:+90 262 646 01 00

2. COMPOSITION / INFORMATION ABOUT INGREDIENTS

A mixture of base oil and performance additives.

CAS NO. / EC NO.	Chemical Composition	% Rate	Symbol(s)	Risk Phrase(s)
Mixture	Base Oil	65-95	-	-
68649-42-3 / 272-028-3	Zinc alkyldithiophosphate	<=1,6	N, Xi	R51/53 R36/38 R41
Proprietary	Methacrylate copolymer	<=0,1	Xi	R36

ULTRA OIL GEARTECH EP 85W-90 GL-5

Date of Issue: 08.01.2021

3. HAZARDS IDENTIFICATION

Physical / Chemical HazardsNot classified as dangerous.Human health hazardsNot classified as dangerous

Environmental Hazards Not likely to be harmful to aquatic organisms.

4. FIRST-AID MEASURES

Eye contact Hold the eyelids apart with clean hands and flush with running water

for at least 15 minutes.

Skin contact Rinse thoroughly with running water and soap. Take off contaminated

clothes and should be washed contacted area on skin with water. You

should see the doctor if irritate keeps continue on the skin.

Ingestion DO NOT induce vomiting! Wash the mouth out with water. In case of

nausea or any other symptoms seek medical assistance and show the

label/container.

Inhalation Remove the person to fresh air. If the person has breathing difficulties,

seek medical assistance.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishers And Fire

Fighting Method

Should be used foam, dry chemical and water spry at small-scale fires $% \left(1\right) =\left(1\right) \left(1\right) +\left(1\right) \left(1\right) \left(1\right) +\left(1\right) \left(

Should call fire department at large fire.

Unsuitable Extinguishers And Fire

Fighting Method

Do not intervene fire with water.

Special Situations After Combustion

Special protective equipment for Fire-

fighting

Toxic gases consist After Combustion. May burn at high temperatures.

Should be used protective clothing and oxygen mask for extinguishing

Indoor locations fires by trained personnel.

ULTRA OIL GEARTECH EP 85W-90 GL-5

Date of Issue: 08.01.2021

6. ACCIDENTAL RELEASE MEASURES

Personal precautionsUse personal protective equipment from item 8. Stand upwind from the

release site.

Environmental precautions Avoid spilling into water, sewerage and drainage systems by digging a

protective ditch and/or setting up partitions of dry sand, soil or similar

absorbent material. Use floating dams for water spills.

Methods for cleaning-up and recovery Absorb the spilt product with absorbent or inert material. Store the

waste material and contaminated surface layer of soil that was removed in closed containers in well-ventilated premises. Hand over for disposal to legal entities for hazardous waste disposal, authorized by the Ministry

in charge of environmental protection.

Additional warnings In case of larger spills, notify the communication unit at 112.

7. HANDLING AND STORAGE

Handling

Safety precautions Use product in well ventilated premises. Keep away from sources of

heat and ignition.

Safe handling advice Avoid contact with skin and eyes.

Storage: Technical measures and storage conditions

Suitable It is recommended that base oil be stored in covered or closed area.

Recommended storage temperature is 5-40 °C.

To be avoided Do not expose to direct sunlight or higher temperatures, avoid contact

with water or strong oxidants.

Packaging materials

Recommended Material resistant to hydrocarbons.

Not suitable Anything else.

ULTRA OIL GEARTECH EP 85W-90 GL-5

Date of Issue: 08.01.2021

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Technical measures for reducing exposure Ensure good ventilation of premises.

Control parameters See item 7.

Personal protective equipment

Respiratory protection During regular work respiratory protective equipment is not required.

In special cases (e.g. spills) use full face protective mask and in case of

fire self-contained pressurized air breathing apparatus.

Hand protection Gloves made of PVC or neoprene, resistant to oils, greases, alkali and

acids.

Eye protection Protective goggles with side protection or protective visor.

Skin and body protection Protective clothes and footwear.

Special hygienic and safety precautions Smoking, eating and drinking is prohibited during handling this

product. Wash hands before each work break.

Additional warnings Immediately remove contaminated clothes and footwear.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical properties

State: Liquid Color: Amber Odor: Petroleum odor

ULTRA OIL GEARTECH EP 85W-90 GL-5

Date of Issue: 08.01.2021

Chemical properties

Characteristics	Unit	Values	Method
Density @ 15 ºC	g/cm3	0,90	ASTM D 4052
Flash Point	o€C	Min. 220	ASTM D 92
Kinematic Viscosity@100 ºC	mm2/s	24,0-32,5	ASTM D 445

10. STABILITY AND REACTIVITY,

Stability Stabile at normal conditions.

Conditions to avoid High temperature and direct sunlight.

Materials to avoid Avoid contact with water and strong oxidants.

Hazardous decomposition products Forming of dangerous products not expected at normal storage

conditions.

11. TOXICOLOGICAL INFORMATION

Eye contact If accidental eye contact can cause temporary blindness.

Skin contact Prolonged or repeated contact can cause skin irritation. If skin contact

with hot product that creates skin burns.

Ingestion There is no any information.

Respiratory Eye, nose and throat will be irritated if fog or mist breathes. Hot

product vapor irritates the upper respiratory tract.

ULTRA OIL GEARTECH EP 85W-90 GL-5

Date of Issue: 08.01.2021

12. ECOLOGICAL

Ecotoxicity Does not harm the aquatic life forms. Spills make film layer on water

and prevent oxygen transfer.

Mobility Spilled product will cause pollution of groundwater.

Persistence and degradabilityHave the ability to accumulate in the soil.

13. DISPOSAL CONSIDERATIONS

According to current legislation should be eliminated by licensed personnel.

14. TRANSPORT INFORMATION

Transportation is not dangerous. Not classified as hazardous for transport.

15. REGULATORY INFORMATION

S2 Keep out of the reach of children

S26 In case of contact with eyes, rinse immediately with plenty of water

and seek medical advice.

S29 Do not empty into drains.

Wear eye/face protection.

S46 If swallowed, seek medical advice immediately and show this container

or label

ULTRA OIL GEARTECH EP 85W-90 GL-5

Date of Issue: 08.01.2021

16. OTHER INFORMATION

Relevant R Phrases

R41 Risk of serious damage to eye.

R38 Irritating to skin

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of this company's knowledge and believed accurate and reliable as of the date indicated. However, no representation, warranty or guarantee is made as to the accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitableness and completeness of such information for his own particular use.