



ULTRA OIL MOTO 4T 20W-50 SL/CF

Product Description and Area of Use

It is a 4-stroke motorcycle oil formulated from highly refined quality base oils and advanced additives to provide excellent engine cleaning, wear and corrosion protection. Suitable for use during all seasons for air-cooled/liquid-cooled 4-stroke engines.

Properties and Benefits

- Ensures high performance in wide temperature ranges.
- It helps to keep the engine clean by controlling the formation of sludge and residues thanks to the improved additive system.
- Effectively protects the engine against corrosion, oxidation, rust and wear and prevents foaming.

Specifications and Approvals Fulfilled API SL/CF , JASO MA2 , JASO MA , API TC

Typical Properties*

<u>TEST</u>	<u>UNIT</u>	<u>TEST METHOD</u>	<u>TYPICAL VALUES</u>
Density, @15 °C	g/cm ³	ASTM 4052	0.875
K. Viscosity, @ 100°C	cSt	ASTM D 445	16.3-21.9
Viscosity Index		ASTM D 2270	125
Flashing Point	°C	ASTM D 92	230
Pour Point	°C	ASTM D 97	-27

* Values may vary between productions.

Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.