



ULTRA OIL RED GREASE 1-2-3

Product Description and Field of Use

Red colored grease prepared from high quality base oils and calcium soap additives. It is used in low speed flat bearings and chassis lubrication, lubrication of bearings operating at average and high speeds under operating conditions where the temperature is not high.

Properties and Benefits

- Provides high resistance to corrosion and water.
- Suitable for low and medium speed bearings with operating temperatures not exceeding 70°C, low speed flat bearings and chassis applications.
- Reduces corrosion by minimizing maintenance costs.
- It reduces the expenditures adhering to the surface thanks to its fibrous structure.

Typical Properties*

TEST	UNIT	TEST METHOD	TYPICAL VALUES		
NLGI			1	2	3
SOAP TYPE		-	Ca	Ca	Ca
COLOR			Red	Red	Red
Worked Penetration, (25°C, 60 strokes)		ASTM D217	310-340	265-295	220-250
Drip Point (°C)	°C	ASTM D566	85	90	90

* Values may vary between productions.

Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.